

**Angel and Shreiner: Interactive Computer Graphics, Seventh
Edition**

Chapter 1 Odd Solutions

1.1 In full-color systems, there are 24 (or more) bits per frame buffer.

1.3 We derive this algorithm later in Chapter 6. First, we can form the tetrahedron by finding four equally spaced points on a unit sphere centered at the origin. One approach is to start with one point on the z axis $(0, 0, 1)$. We then can place the other three points in a plane of constant z . One of these three points can be placed on the y axis. To satisfy the requirement that the points be equidistant, the point must be at $(0, 2\sqrt{2}/3, -1/3)$. The other two can be found by symmetry to be at $(-\sqrt{6}/3, -\sqrt{2}/3, -1/3)$ and $(\sqrt{6}/3, -\sqrt{2}/3, -1/3)$.

We can subdivide each face of the tetrahedron into four equilateral triangles by bisecting the sides and connecting the bisectors. However, the bisectors of the sides are not on the unit circle so we must push these points out to the unit circle by scaling the values. We can continue this process recursively on each of the triangles created by the bisection process.

1.5 In Exercise 1.4, we saw that we could intersect the line of which the line segment is part independently against each of the sides of the window. We could do this process iteratively, each time shortening the line segment if it intersects one side of the window.

1.7 In a one-point perspective, two faces of the cube is parallel to the projection plane, while in a two-point perspective only the edges of the cube in one direction are parallel to the projection. In the general case of a three-point perspective there are three vanishing points and none of the edges of the cube are parallel to the projection plane.

1.9 Each frame for a 600 x 800 pixel computer video display contains only about 480,000 pixels, whereas the 2000 x 3000 pixel movie frame has 6,000,000 pixels, or approximately 12.5 times as many as there are in the computer video display. Thus, it can take 12.5 times as much time to render each frame if there are many pixel-level calculations.

1.11 A 600 x 800 display has a 3 to 4 aspect ratio. Hence, if the diagonal is 50 cm and we want square pixels, the screen must be approximately 30 cm x 40 cm. Each pixel is then about 0.5 mm on each side. A smooth display will require about 3 triads for each pixel, and thus the triads are about 0.167 mm apart. Finally if the shadow mask is halfway between the screen and electron guns, the shadow mask spacing is half the triad spacing.