

Solutions Manual[©]

to accompany

System Dynamics, Third Edition

by

William J. Palm III

University of Rhode Island

Solutions to Problems in Chapter One

©Solutions Manual Copyright 2013 The McGraw-Hill Companies. All rights reserved. No part of this manual may be displayed, reproduced, or distributed in any form or by any means without the written permission of the publisher or used beyond the limited distribution to teachers or educators permitted by McGraw-Hill for their individual course preparation. Any other reproduction or translation of this work is unlawful.

1.1 $W = mg = 3(32.2) = 96.6 \text{ lb.}$

1.2 $m = W/g = 100/9.81 = 10.19 \text{ kg.}$ $W = 100(0.2248) = 22.48 \text{ lb.}$ $m = 10.19(0.06852) = 0.698 \text{ slug.}$

1.3 $d = (50 + 5/12)(0.3048) = 15.37 \text{ m.}$

1.4 $d = 3(100)(0.3048) = 91.44 \text{ m}$

1.5 $d = 100(3.281) = 328.1 \text{ ft}$

1.6 $d = 50(3600)/5280 = 34.0909 \text{ mph}$

1.7 $v = 100(0.6214) = 62.14 \text{ mph}$

1.8 $n = 1/[60(1.341 \times 10^{-3})] = 12.43$, or approximately 12 bulbs.

1.9 $5(70 - 32)/9 = 21.1^\circ \text{ C}$

1.10 $9(30)/5 + 32 = 86^\circ \text{ F}$

1.11 $\omega = 3000(2\pi)/60 = 314.16 \text{ rad/sec.}$ Period $P = 2\pi/\omega = 60/3000 = 1/50 \text{ sec.}$

1.12 $\omega = 5 \text{ rad/sec.}$ Period $P = 2\pi/\omega = 2\pi/5 = 1.257 \text{ sec.}$ Frequency $f = 1/P = 5/2\pi = 0.796 \text{ Hz.}$

1.13 Speed $= 40(5280)/3600 = 58.6667 \text{ ft/sec.}$ Frequency $= 58.6667/30 = 1.9556 \text{ times per second.}$

1.14 $x = 0.005 \sin 6t$, $\dot{x} = 0.005(6) \cos 6t = 0.03 \cos 6t$. Velocity amplitude is 0.03 m/s. $\ddot{x} = -6(0.03) \sin 6t = -0.18 \sin 6t$. Acceleration amplitude is 0.18 m/s^2 . Displacement, velocity and acceleration all have the same frequency.

1.15 Physical considerations require the model to pass through the origin, so we seek a model of the form $f = kx$. A plot of the data shows that a good line drawn by eye is given by $f = 0.2x$. So we estimate k to be 0.2 lb/in.

1.16 The script file is

```
x = [0:0.01:1];
subplot(2,2,1)
plot(x,sin(x),x,x),xlabel('x (radians)'),ylabel('x and sin(x)'),...
gtext('x'),gtext('sin(x)')
subplot(2,2,2)
plot(x,sin(x)-x),xlabel('x (radians)'),ylabel('Error: sin(x) - x')
subplot(2,2,3)
plot(x,100*(sin(x)-x)./sin(x)),xlabel('x (radians)'),...
ylabel('Percent Error'),grid
```

The plots are shown in the figure.




Figure : for Problem 1.16.

From the third plot we can see that the approximation $\sin x \approx x$ is accurate to within 5% if $|x| \leq 0.5$ radians.

1.17 For θ near $\pi/4$,

$$f(\theta) \approx \sin \frac{\pi}{4} + \left(\cos \frac{\pi}{4} \right) \left(\theta - \frac{\pi}{4} \right)$$

For θ near $3\pi/4$,

$$f(\theta) \approx \sin \frac{3\pi}{4} + \left(\cos \frac{3\pi}{4} \right) \left(\theta - \frac{3\pi}{4} \right)$$

1.18 For θ near $\pi/3$,

$$f(\theta) \approx \cos \frac{\pi}{3} - \left(\sin \frac{\pi}{3} \right) \left(\theta - \frac{\pi}{3} \right)$$

For θ near $2\pi/3$,

$$f(\theta) \approx \cos \frac{2\pi}{3} - \left(\sin \frac{2\pi}{3} \right) \left(\theta - \frac{2\pi}{3} \right)$$

1.19 For h near 25,

$$f(h) \approx \sqrt{25} + \frac{1}{2\sqrt{25}}(h - 25) = 5 + \frac{1}{10}(h - 25)$$

1.20 For r near 5,

$$f(r) \approx 5^2 + 2(5)(r - 5) = 25 + 10(r - 5)$$

For r near 10,

$$f(r) \approx 10^2 + 2(10)(r - 10) = 100 + 20(r - 10)$$

1.21 For h near 16,

$$f(h) \approx \sqrt{16} + \frac{1}{2\sqrt{16}}(h - 16) = 4 + \frac{1}{8}(h - 16)$$

$f(h) \geq 0$ if $h > -16$.

1.22 Construct a straight line that passes through the two endpoints at $p = 0$ and $p = 900$. At $p = 0$, $f(0) = 0$. At $p = 900$, $f(900) = 0.002\sqrt{900} = 0.06$. This straight line is

$$f(p) = \frac{0.06}{900}p = \frac{1}{15,000}p$$

1.23 (a) The data is described approximately by the linear function $y = 54x - 1360$. The precise values given by the least squares method (Appendix C) are $y = 53.5x - 1354.5$.

(b) Only the loglog plot of the data gives something close to a straight line, so the data is best described by a power function $y = bx^m$ where the approximate values are $m = -0.98$ and $b = 3600$. The precise values given by the least squares method (Appendix C) are $y = 3582.1x^{-0.9764}$.

(c) Both the loglog and semilog plot (with the y axis logarithmic) give something close to a straight line, but the semilog plot gives the straightest line, so the data is best described by an exponential function $y = b(10)^{mx}$ where the approximate values are $m = -0.007$ and $b = 2.1 \times 10^5$. The precise values given by the least squares method (Appendix C) are $y = 2.0622 \times 10^5(10)^{-0.0067x}$.

1.24 With this problem, it is best to scale the data by letting $x = \text{year} - 2005$, to avoid raising large numbers like 2005 to a power. Both the loglog and semilog plot (with the y axis logarithmic) give something close to a straight line, but the semilog plot gives the straightest line, so the data is best described by an exponential function $y = b(10)^{mx}$. The approximate values are $m = 0.035$ and $b = 9.98$.

Set $y = 20$ to determine how long it will take for the population to increase from 10 to 20 million. This gives $20 = 9.98(10)^{0.035x}$. Solve it for x : $x = (\log(20) - \log(9.98))/0.035$. The answer is 8.63 years, which corresponds to 8.63 years after 2005.

1.25 (a) If $C(t)/C(0) = 0.5$ when $t = 500$ years, then $0.5 = e^{-5500b}$, which gives $b = -\ln(0.5)/5500 = 1.2603 \times 10^{-4}$.

(b) Solve for t to obtain $t = -\ln[C(t)/C(0)]/b$ using $C(t)/C(0) = 0.9$ and $b = 1.2603 \times 10^{-4}$. The answer is 836 years. Thus the organism died 836 years ago.

(c) Using $b = 1.1(1.2603 \times 10^{-4})$ in $t = -\ln(0.9)/b$ gives 760 years. Using $b = 0.9(1.2603 \times 10^{-4})$ in $t = -\ln(0.9)/b$ gives 928 years.

1.26 Only the semilog plot of the data gives something close to a straight line, so the data is best described by an exponential function $y = b(10)^{mx}$ where y is the temperature in degrees C and x is the time in seconds. The approximate values are $m = -3.67$ and $b = 356$. The alternate exponential form is $y = be^{(m \ln 10)x} = 356e^{-8.451x}$. The time constant is $1/8.451 = 0.1183$ s.

The precise values given by the least squares method (Appendix C) are $y = 356.0199(10)^{-3.6709x}$.

1.27 Only the semilog plot of the data gives something close to a straight line, so the data is best described by an exponential function $y = b(10)^{mx}$ where y is the bearing life thousands of hours and x is the temperature in degrees F. The approximate values are $m = -0.007$ and $b = 142$. The bearing life at 150° F is estimated to be $y = 142(10)^{-0.007(150)} = 12.66$, or 12,600 hours. The alternate exponential form is $y = be^{(m \ln 10)x} = 142e^{-0.0161x}$. The time constant is $1/0.0161 = 62.1$ or 6.21×10^4 hr.

The precise values given by the least squares method (Appendix C) are $y = 141.8603(10)^{-0.0070x}$.

1.28 Only the semilog plot of the data gives something close to a straight line, so the data is best described by an exponential function $y = b(10)^{mx}$ where y is the voltage and x is the time in seconds. The first data point does not lie close to the straight line on the semilog plot, but a measurement error of ± 1 volt would account for the discrepancy. The approximate values are $m = -0.43$ and $b = 96$. The alternate exponential form is $y = be^{(m \ln 10)x} = 96e^{-0.99x}$. The time constant is $1/0.99 = 1.01$ s.

The precise values given by the least squares method (Appendix C) are $y = 95.8063(10)^{-0.4333x}$.

1.29 A semilog plot generated by the following script file shows that the exponential function $T - 70 = be^{mt}$ fits the data well.

```
t = [0:300:3000];  
temp = [207,182,167,155,143,135,128,123,118,114,109];  
DT = temp-70;  
semilogy(t,DT,t,DT,'o')
```

Fitting a line by eye gives the approximate values $m = -4 \times 10^{-4}$ and $b = 125$. The corresponding function is $T(t) = 70 + 125e^{-4 \times 10^{-4}t}$.

The precise values given by the least squares method (Appendix C) are $m = -4.0317 \times 10^{-4}$ and $b = 125.1276$.

1.30 Plots of the data on a log-log plot and rectilinear scales both give something close to a straight line, so we try both functions. (Note that the flow should be 0 when the height is 0, so we do not consider the exponential function and we must force the linear function to pass through the origin by setting $b = 0$.) The three lowest heights give the same time, so we discard the heights of 1 and 2 cm.

The power function fitted by eye in terms of the height h is approximately $f = 4h^{0.9}$. Note that the exponent is not close to 0.5, as it is for orifice flow. This is because the flow through the outlet is pipe flow. For the linear function $f = mh$, the best fit by eye is approximately $f = 3.2h$.

Using the least squares method (Appendix C) gives more precise results: $f = 4.1595h^{0.8745}$ and $f = 3.2028h$.

1.31 Plots of the data on a log-log plot and rectilinear scales both give something close to a straight line, so we try both functions. (Note that the flow should be 0 when the height is 0, so we do not consider the exponential function and we must force the linear function to pass through the origin by setting $b = 0$.) The variable x is the height and the variable y is the flow rate. The three lowest heights give the same time, so we discard the heights of 1 and 2 cm.

The power function fitted by eye in terms of the height h is approximately $f = 4h^{0.9}$. Note that the exponent is not close to 0.5, as it is for orifice flow. This is because the flow through the outlet is pipe flow. For the linear function $f = mh$, the best fit by eye is approximately $f = 3.7h$.

Using the least squares method (Appendix C) gives more precise results: $f = 4.1796h^{0.9381}$ and $f = 3.6735h$.